| NOTES: 1-19)-FAM MOTOR LOCATION 2- MIT DENOTES MALE PIPE THREAD BRY DENOTES RAME PIPE THREAD BRY DENOTES REVELED FOR WELDING GVD DENOTES REVELED FOR WELDING GVD DENOTES RAMES 1-19 DENOTES FLANCE 3-10 DENOTES FLANCE 4-1-1 J./4" 1-10 DENOTES FLANCE 3-10 DENOTES FLANCE 1-10 DENOTES FLANCE 1-1 | UNIT | COOLING TOV | VER | EVADOO TNO | evapco | DWG. # | TV08093F-DRJ-ST | REV |
|--|---|--|--|-----------------------------|---|----------|-----------------|--------------------|
| 1. (M) - FAM MOTOR LOCATION MY DENOTES MALE PIPE THREAD BY DENOTES FEMALE PIPE THREAD BY DENOTES | MODEL # | LPT-879 | SCALE NTS | EVAPCO, INC | | SERIAL # | | DATE 5/21/2024 |
| 3'-11" (1195) 8" [200] BFW/GVD INLET 7'-5/8" (2149) 3" [75] MPT OVERFLOW OUTLET 3'-1/4" (919) (6'-3") ACCESS DOOR 6'-7-3/4 (2026) 3" [75] MPT OVERFLOW OVERFLOW OUTLET | 1. (M)- FAN MC 2. MPT DENOTI FPT DENOTE BFW DENOT GVD DENOT FLG DENOTE 3. + UNIT WEI ACCESSORIE FOR ACCESS 4. 3/4" DIA. MC RECOMMENT DRAWING 5. MAKE-UP WA 50 psi MAX 6. DIMENSION ENGLI: | ES MALE PIPE THREAD ES FEMALE PIPE THREAD ES FEMALE PIPE THREAD ES GROOVED ES GROOVED ES FLANGE GHT DOES NOT INCLUI ES (SEE SEPARATE DRA GORIES) DUNTING HOLES. REFI DED STEEL SUPPORT ATER PRESSURE-20 psi IS LISTED AS FOLLO SH FT-IN | AD DING DE AWINGS ER TO I MIN, | | FA | CE C | | FACE D |
| 7 1/4" 3'-11" 2 5/8" 1'-8 1/8" 1'-8 1/8" 4'-11 1/2" 4'-11 1/2" 4'-11 1/2" 5'-7 1/2" 5'-7 1/2" 1714] | 3 1/4" [83] 3'-1/4" [919] | TYP 8" | 8" [200] BFW/GVD INLET [200] BFW/GVD OUTLET | 7'-11 1/2" 7'-5/8" [2149] | ACCESS DOOR 2" [50] MPT DRAIN 3" [75] MPT OVERFLOW 4'-11 1/2" [1511] | | ACCESS DOOR | 6'-7 3/4" [2026] |

HEAVIEST SECTION WEIGHT

SHIPPING WEIGHT OPERATING WEIGHT

7890 lbs+ [3580] kg+

4490 lbs+ [2040] kg+

FACE A

4490 lbs+ [2040] kg+

NO. OF SHIPPING SECTIONS

DRAWN BY: JLG